
libgravatar Documentation

Release 0.2.5

Pablo SEMINARIO

Apr 09, 2021

Contents

1 Indices and tables	3
Python Module Index	5
Index	7

Contents: A library that provides a Python 3 interface to the Gravatar APIs.

class libgravatar.Gravatar(*email*)

This class encapsulates all the unauthenticated methods from the API.

get_image(*size*=80, *default*='', *force_default*=False, *rating*='', *filetype_extension*=False, *use_ssl*=False)

Returns an URL to the user profile image.

```
>>> g = Gravatar('myemailaddress@example.com')
>>> g.get_image()
'http://www.gravatar.com/avatar/0bc83cb571cd1c50ba6f3e8a78ef1346'
```

With *size* you can request a specific image size, by default, images are presented at 80px by 80px. You may request image anywhere from 1px up to 2048px.

The *default* parameter is used to supply a default image when an email address has no match Gravatar image. *default* can be an URL or one of the built in options *404*, *mm*, *mp*, *identicon*, *monsterid*, *wavatar*, *robohash*, *retro* or *blank*.

force_default force the default image to always load.

rating can be used to request images by audience type. Possible values are *g*, *pg*, *r* or *x*. By default, only *g* rated images are displayed.

filetype_extension add an optional *.jpg* extension.

use_ssl can be used to request images via SSL.

See more details on [Gravatar Image Requests](#).

get_profile(*data_format*=")

Returns an URL to the profile information associated with the Gravatar account.

```
>>> g = Gravatar('myemailaddress@example.com')
>>> g.get_profile()
'http://www.gravatar.com/0bc83cb571cd1c50ba6f3e8a78ef1346'
```

See more details on [Gravatar Profile Requests](#).

class libgravatar.GravatarXMLRPC(*email*, *apikey*='', *password*='')

This class encapsulates all the authenticated methods from the XML-RPC API.

API details: <http://en.gravatar.com/site/implement/xmlrpc>

addresses()

Gets a list of addresses for this account.

exists(*hashes*)

Checks whether a hash has a gravatar.

test()

Test the API.

userimages()

Returns a dict of userimages for this account.

libgravatar.default_url_is_valid(*url*)

Gravatar conditions for valid default URLs.

```
>>> default_url_is_valid('http://example.com/images/avatar.jpg')
True
```

`libgravatar.md5_hash(string)`

Returns a md5 hash from a string.

```
>>> md5_hash('myemailaddress@example.com')
'0bc83cb571cd1c50ba6f3e8a78ef1346'
```

`libgravatar.sanitize_email(email)`

Returns an e-mail address in lower-case and strip leading and trailing whitespaces.

```
>>> sanitize_email(' MyEmailAddress@example.com ')
'myemailaddress@example.com'
```

CHAPTER 1

Indices and tables

- genindex
- modindex
- search

Python Module Index

|

libgravatar, 1

Index

A

addresses () (*libgravatar.GravatarXMLRPC method*), 1

D

default_url_is_valid () (*in module libgravatar*),
1

E

exists () (*libgravatar.GravatarXMLRPC method*), 1

G

get_image () (*libgravatar.Gravatar method*), 1
get_profile () (*libgravatar.Gravatar method*), 1
Gravatar (*class in libgravatar*), 1
GravatarXMLRPC (*class in libgravatar*), 1

L

libgravatar (*module*), 1

M

md5_hash () (*in module libgravatar*), 1

S

sanitize_email () (*in module libgravatar*), 2

T

test () (*libgravatar.GravatarXMLRPC method*), 1

U

userimages () (*libgravatar.GravatarXMLRPC method*), 1